

/

•

•

— 3 —

)

-1

• (

-2

•

$$-:$$

-1

•

-2

•

-3

.

-:

-1

.

-2

.

-3

.

-4

.

-5

.

-6

-7

.

-8

.

.

.

.

)

(

.

.

.

$-\dot{}$

-1

.

(1)

. [1]

-2

.

1.5

5

. 19

[2] 4

(1)

.

7

19

. 15

.

43

(2) 83

.

.

(2)

.

(3)

130-80

-2

quality Plants people & Environmental

Gary

5-2

Gregory

30

2

7

(pre heating)

(pre cooling)

.

:

-1

(4)

6

9

18

(9)

% 53

(9)

.

.(1)

-2

()

[5]

.

-

. [2]

-3

(5)

.

(%100-%10)

[6]

-4

(2 1x1)

(6)

. [7]

-5

(7)

2 2.8

(1.4x2)

(2x1.4)

% 36

% 16

. [8]

-6

(8)

(9)

.

9

6

400

.

%85

368 ()
) %20

(1

.

-7

.

(3)

.

.

-8

Lime Glass

)

0,3

(

0.313-0,288

)

(

-9

43

84

59

-10

.

(10)

.

2 360

162,525

(12,13 11)

- 1- Al-Jawadi M.& Al-Noah A. , The Proper Plot and House Proportions and Orientations for Latitude 30 to 36 N , Energy Resources and Conservation Related to Built Environment pp 1192-1209 ,Pergamon Press 1980 U.S.A .
-2
3 4
- 1989 58-37
- 3- Gary, Plants People & Environmental Quality' U.S. Department of the Interior. 1980' U.S.A.
-4
- 2001
-5
- 2001
-6
2
- 2001

7-AL-Jawadi & Al-Noah The Best Window Proportion
for Latitude 30-36 N, Proceeding of the Housing
Conference ,Miami Beach , Pergamon press ,1979
U.S.A.

. -8

. - 1994 4

. - -9